



ПЕРЕКЛЮЧАТЕЛИ

№ Модели	Описание	Частота(МГц)		Вносимые потери (dB) Норм.	Изоляция (dB) Норм.	КСВ Вх/Вых	Время переключения (ns)	Тип питания		Мощность (W) Макс.	Размер (mm)	Частотный диапазон (band)
		Мин.	Макс.					(Vdc)	(mA)			
OC-SWH05-18KA3.5L80	SPST Absorptive	500	18000	3,5	55	2.0:1	80	+5/-5	50/50	0,5	24x15x10	Ku
OC-SWH1-18KA3.2L60-S	SPST Absorptive	1000	18000	3,2	60	2.0:1	80	+5/-5	50/50	0,5	24x15x10	Ku
OC-SWH6-18KA3L60-S	SPST Absorptive	6000	18000	3	60	2.0:1	80	+5/-5	50/50	0,5	24x15x10	Ku
OC-SWH18-40KA5.5L50-S	SPST Absorptive	18000	40000	5,5	50	2.5:1	50	+5/-5	20/20	0,1	24x15x10	Ka
OC-SWH26/5-40KA5.5L50-S	SPST Absorptive	26500	40000	5,5	50	2.5:1	50	+5/-5	20/20	0,1	24x15x10	Ka
OC-SWH05-2KR1.5L50-S	SPST Reflective	500	2000	1,5	50	2.0:1	80	+5/-5	50/50	1	24x15x10	L
OC-SWH1-18KR2.8L50-S	SPST Reflective	1000	18000	2,8	50	2.0:1	80	+5/-5	50/50	1	24x15x10	Ku
OC-SWH05-2KA2L55-D	SPDT Absorptive	500	2000	2	55	2.0:1	80	+5/-5	70/70	0,5	24x15x10	L
OC-SWH1-18KA3.3L55-D	SPDT Absorptive	1000	18000	3,3	55	2.0:1	80	+5/-5	70/70	0,5	24x15x10	Ku
OC-SWH18-26.5K5L55-D	SPDT Absorptive	18000	26500	5	55	2.5:1	50	+5/-5	20/20	0,1	24x15x10	K
OC-SWH26.5-40KA5.5L50-D	SPDT Absorptive	26500	40000	5,5	50	2.5:1	50	+5/-5	20/20	0,1	24x15x10	Ka
OC-SWH05-2KR1.5L55-D	SPDT Reflective	500	2000	1,5	55	2.0:1	80	+5/-5	70/70	1	24x15x10	L
OC-SWH1-18KR3L60-D	SPDT Reflective	1000	18000	3	60	2.0:1	80	+5/-5	70/70	1	24x15x10	Ku
OC-SWH18-26.5KR5L55-D	SPDT Reflective	18000	26500	5	55	2.5:1	50	+5/-5	20/20	0,1	24x15x10	K
OC-SWH26.5-40KR5.5L50-D	SPDT Reflective	26500	40000	5,5	50	2.5:1	50	+5/-5	20/20	0,1	24x15x10	Ka
OC-SWH05-2KA1.5L55-3	SP3T Absorptive	500	2000	1,5	55	2.0:1	80	+5/-5	100/50	0,5	33x26x12	L
OC-SWH1-18KA3.5L55-3	SP3T Absorptive	1000	18000	3,5	55	2.0:1	80	+5/-5	100/50	0,5	33x26x12	Ku
OC-SWH05-2KR1.3L55-3	SP3T Reflective	500	2000	1,3	55	2.0:1	80	+5/-5	100/50	1	33x26x12	L
OC-SWH1-18KR3L55-3	SP3T Reflective	1000	18000	3	55	2.0:1	80	+5/-5	100/50	1	33x26x12	Ku
OC-SWH05-2KA1.6L55-4	SP4T Absorptive	500	2000	1,6	55	2.0:1	80	+5/-5	150/50	0,5	43x28x12	L
OC-SWH1-18KA3.6L55-4	SP4T Absorptive	1000	18000	3,6	55	2.0:1	80	+5/-5	150/50	0,5	43x28x12	Ku
OC-SWH05-2KR1.5L55-4	SP4T Reflective	500	2000	1,5	55	2.0:1	80	+5/-5	150/50	1	43x28x12	L



ПЕРЕКЛЮЧАТЕЛИ

№ Модели	Описание			Вносимые потери (dB) Норм.	Изоляция (dB) Норм.	КСВ Вх/Вых	Время переключения (ns)			Мощность (W) Макс.	Размер (mm)	Частотный диапазон (band)
		Мин.	Макс.					(Vdc)	(mA)			
OC-SWH1-18KR3.3L55-4	SP4T Reflective	1000	18000	3,3	55	2.0:1	80	+5/-5	150/50	1	43x28x12	Ku
OC-SWH05-2KA2L55-5	SP5T Absorptive	500	2000	2	55	2.0:1	80	+5/-5	200/50	0,5	53x30x14	L
OC-SWH1-18KA3.8L55-5	SP5T Absorptive	1000	18000	3,8	55	2.0:1	80	+5/-5	200/50	0,5	53x30x14	Ku
OC-SWH05-2KR1.8L55-5	SP5T Reflective	500	2000	1,8	55	2.0:1	80	+5/-5	200/50	1	53x30x14	L
OC-SWH1-18KR3.7L55-5	SP5T Reflective	1000	18000	3,7	55	2.0:1	80	+5/-5	200/50	1	53x30x14	Ku
OC-SWH05-2KA2.2L55-6	SP6T Absorptive	500	2000	2,2	55	2.0:1	80	+5/-5	250/50	0,5	63x34x14	L
OC-SWH1-18KA4.2L55-6	SP6T Absorptive	1000	18000	4,2	55	2.0:1	80	+5/-5	250/50	0,5	63x34x14	Ku
OC-SWH05-2KR2.1L55-6	SP6T Reflective	500	2000	2,1	55	2.0:1	80	+5/-5	250/50	1	63x34x14	L
OC-SWH1-18KR4L55-6	SP6T Reflective	1000	18000	4	55	2.0:1	80	+5/-5	250/50	1	63x34x14	Ku
OC-SWH05-2KA2.4L55-7	SP7T Absorptive	500	2000	2,4	55	2.0:1	80	+5/-5	300/70	0,5	76x38x14	L
OC-SWH1-18KA4.6L55-7	SP7T Absorptive	1000	18000	4,6	55	2.0:1	80	+5/-5	300/70	0,5	76x38x14	Ku
OC-SWH05-2KR2.3L55-7	SP7T Reflective	500	2000	2,3	55	2.0:1	80	+5/-5	300/70	1	76x38x14	L
OC-SWH1-18KR4.3L55-7	SP7T Reflective	1000	18000	4,3	55	2.0:1	80	+5/-5	300/70	1	76x38x14	Ku
OC-SWH05-2KA2.5L55-8	SP8T Absorptive	500	2000	2,5	55	2.0:1	80	+5/-5	400/100	0,5	88x38x14	L
OC-SWH1-18KA4.8L55-8	SP8T Absorptive	1000	18000	4,8	55	2.0:1	80	+5/-5	400/100	0,5	88x38x14	Ku
OC-SWH05-2KR2.4L55-8	SP8T Reflective	500	2000	2,4	55	2.0:1	80	+5/-5	400/100	1	88x38x14	L
OC-SWH1-18KR4.5L55-8	SP8T Reflective	1000	18000	4,5	55	2.0:1	80	+5/-5	400/100	1	88x38x14	Ku