



ТРАНСИВЕРЫ

Наименование	Частота (MHz)		P1 (dBm)		Усиление (dB)		Коэффициент шума (NF) (dB)	Напряжение (V)	Ток норм. (A)	Размер (mm)	Частотный диапазон (band)
	Мин.	Макс.	Прием Rx	Передача Tx	Прием Rx	Передача Tx					
OC-TR0225-04K10/43DB	225	400	10	43	10	45	2,5	28	3	150 x 90 x 27	UHF
OC-TR0225-04K10/47DB	225	400	10	47	22	49	2,5	28	8	180x 150 x 27	
OC-TR06-08K10/45DB	600	800	10	43	10	45	2,5	28	3	150 x 90 x 27	L
OC-TR06-08K20/47DB	600	800	20	47	22	49	2,5	28	8	180x 150 x 27	
OC-TR06-08K25/50DB	600	800	25	50	27	52	3	28	15	200x 160 x 27	
OC-TR089-096K10/43DB	890	960	10	43	10	45	2,5	28	3	150 x 90 x 27	L
OC-TR089-096K20/47DB	890	960	20	47	22	49	2,5	28	8	180x 150 x 27	
OC-TR089-096K25/50DB	890	960	25	50	27	52	3	28	15	200x 160 x 27	
OC-TR1.2-1.4K10/43DB	1200	1400	10	43	10	45	2,5	28	3	150 x 100 x 22	L
OC-TR1.2-1.4K20/47DB	1200	1400	20	47	22	49	2,5	28	7	160 x 120 x 22	
OC-TR1.2-1.4K25/50DB	1200	1400	25	50	27	52	3	28	16	180 x 150 x 22	
OC-TR1.2-1.4K10/54DB	1200	1400	10	54	45	54	2,5	50	10	200 x 150 x 22	
OC-TR1.2-1.6K10/43DB	1200	1600	10	43	10	45	3	28	5	150 x 120 x 22	L
OC-TR1.2-1.6K20/47DB	1200	1600	20	47	22	49	3	28	8	160 x 150 x 22	
OC-TR2-6K10/40DB	2000	6000	10	40	30	40	3,5	28	3	180 x 90 x 22	S
OC-TR2.3-2.7K12/47DB	2300	2700	12	47	10	49	3	28	8	160 x 120 x 22	S
OC-TR2.3-2.7K20/50DB	2300	2700	20	50	22	52	3	28	13	180 x 150 x 22	
OC-TR2.9-3.3K2/53DB	2900	3300	2	53	25	53	3,5	48	10	180 x 90 x 22	S
OC-TR5.4-5.9K1/43DB	5400	5900	1	43	25	43	3,5	45	3	120 x 80 x 22	C
OC-TR9-9.2K5/42DB	9000	9200	5	42	30	42	3,5	50	1,5	120 x 80 x 22	X