

## 500-2000MHz/200Watt/Module

Model Number: OC-PA05-2K200W

The model OC-PA05-2K200W is a multi-octave high power amplifier operating between 500 MHz and 2000 MHz and offering a wide dynamic Range with 200 Watts typical saturated power. The employment of advanced high power devices in manufacturing ensures this module exceptional power performance long term reliability and high efficiency. It is ideal multi octave broadband high power RF,S Band linear applications.

### FEATURES:

- Broadband & High power;
- High Efficiency;
- Great Linearity;
- Small Size & Light Weight;
- Low Distortion

### ELECTRICAL SPECIFICATIONS @ +28.0VDC, 25°C, 50Ω

| Parameter                 | Symbol           | Min | Typ | Max  | Units |
|---------------------------|------------------|-----|-----|------|-------|
| Operating Frequency       | BW               | 500 |     | 2000 | MHz   |
| RF Output Power           | P <sub>out</sub> |     | 200 |      | Watt  |
| Power Gain                | G <sub>p</sub>   |     | 53  |      | dB    |
| Power Gain Flatness       | Δ G <sub>p</sub> |     | ±2  |      | dB    |
| Input Return Loss         | S <sub>11</sub>  |     |     | -10  | dB    |
| Harmonics @130W           | H                |     | -12 |      | dBc   |
| Spurious Signals          | Spur             |     | -60 |      | dBc   |
| Switch On/Off@10-90% Time | TON/OFF          |     | 2   | 5    | μS    |
| In/Output Impedance       | Impedance        |     | 50  |      | Ω     |
| Operating Voltage         | V <sub>DC</sub>  | 24  | 28  | 32   | Volt  |
| DC Current @150W          | I <sub>DD</sub>  |     | 24  |      | Amp   |

### MECHANICAL SPECIFICATIONS

| Parameter              | Value                                     | Units     | Notes   |
|------------------------|---|-----------|---------|
| Dimensions             | 250x180x25                                | mm [inch] | Maximum |
| Weight                 | 4 [8.8]                                   | kg [lbs]  | Maximum |
| RF Connectors Input    | SMA, Female                               |           |         |
| RF Connectors Output   | Type-N Female                             |           |         |
| DC Interface Connector | Hybrid, D-sub 7 Pin, Male                 |           |         |
| Cooling                | External Heatsink Required (Not Supplied) |           |         |

### ENVIRONMENTAL CHARACTERISTICS (Design to Meet)

| Parameter                          | Minimum | Typical | Maximum | Units | Notes   |
|------------------------------------|---------|---------|---------|-------|---------|
| Operating Temperature              | -20     |         | 60      | °C    |         |
| Non-operating Temperature          | -25     |         | 65      | °C    | Storage |
| Relative Humidity (non-condensing) |         |         | 95      | %     |         |

### Absolute Maximum Rating

|                                     |  |
|-------------------------------------|--|
| Input RF drive level without damage | +5 dBm (Max)   |
| Load VSWR @ P <sub>OUT</sub> =100W  | ∞ @ all load phase & amplitude for duration of 1 minutes;<br>3:1 @ all load phase & amplitude continuous |
| Over Temperature                    | 85°C @ heatsink [restored @ 60°C]  |


500-2000MHz/200Watt/Module

Model Number: OC-PA05-2K200W

**DC INTERFACE CONNECTOR**

| Pin # | Description   | Specifications  |
|-------|---------------|---|
| A1    | VDD           | 28VDC   |
| A2    | GND           | Ground  |
| 1     | ENABLE        | Amplifier Enable: TTL Logic High (3.3V) (Internally Pulled-Low) |
| 2     | CURRENT SENSE | Analog voltage relative to IDD @ 100mV per Ampere               |
| 3     | TEMP SENSE    | Analog voltage relative to Module's Temperature @ 10 mV/°C      |
| 4     | NC            | No electrical connection  |
| 5     | GND           | Ground  |


**OUTLINE DRAWING (All dimensions in mm [inch])**



500-2000MHz/200Watt/Module

Model Number: OC-PA05-2K200W

TYPICAL PERFORMANCE PLOTS (For Reference Only)



Note: Adequate heat sink required.