

## 2500-6000MHz/30Watt/Module

Model Number: OC-PA2.5-6K30W

The model OC-PA2.5-6K30W is a multi-octave high power amplifier operating between 2500 MHz and 6000 MHz and offering a wide dynamic Range with 30 Watts typical saturated power. The employment of advanced high power devices in manufacturing ensures this module exceptional power performance, long term reliability and high efficiency. It is ideal for broadband high power S/C Band applications.

### FEATURES:

- Broadband & High power;
- High Efficiency;
- Small Size & Light Weight;
- Low Distortion

### ELECTRICAL SPECIFICATIONS @ +30.0VDC, 25°C, 50Ω System

Parameter	Symbol	Min	Typ	Max	Units
Operating Frequency	BW	2500		6000	MHz
RF Output Power	P <sub>out</sub>		30		Watt
Power Gain	G <sub>p</sub>		45		dB
Power Gain Flatness	Δ G <sub>p</sub>		±3		dB
Input Return Loss	S <sub>11</sub>			-10	dB
Harmonics @25W	H		-15		dBc
Spurious Signals	Spur		-55		dBc
Switch On/Off@10-90% Time	TON/OFF		2		μS
In/Output Impedance	Impedance		50		Ω
Operating Voltage	VDC	28	30	32	Volt
DC Current @30W	IDD		7		Amp

### MECHANICAL SPECIFICATIONS

Parameter	Value	Units	Notes
Dimensions	160x100x25 [6.2x3.9x0.98]	mm [inch]	Maximum
Weight	2 [4.4]	kg [lbs]	Maximum
RF Connectors Input	SMA, Female		
RF Connectors Output	SMA, Female		
DC Interface Connector	Hybrid, D-Sub 7-Pin, Male		
Cooling	External Heatsink Required (Not Supplied)		

### ENVIRONMENTAL CHARACTERISTICS (Design to Meet)

Parameter	Minimum	Typical	Maximum	Units	Notes
Operating Temperature	-20		60	°C	
Non-operating Temperature	-30		65	°C	Storage
Relative Humidity (non-condensing)			95	%	

### ABSOLUTE MAXIMUM RATING

Input RF drive level without damage	+5 dBm (Max)
Load VSWR @ P <sub>OUT</sub> =25W	∞ @ all load phase & amplitude for duration of 1 minute; 3:1 @ all load phase & amplitude continuous
Over Temperature	85°C @ heatsink [restored @ 60°C]


## 2500-6000MHz/30Watt/Module

Model Number: OC-PA2.5-6K30W

### DC INTERFACE CONNECTOR

Pin #	Description	Specifications
A1	VDD	30V <sub>DC</sub>
A2	GND	Ground
1	ENABLE	Amplifier Enable: TTL Logic High (3.3V) (Internally Pulled-Low)
2	TEMP SENSE	Analog voltage relative to Module's Temperature @ 10 mV/°C
3	CURRENT SENSE	Analog voltage relative to I <sub>DD</sub> @ 100mV per Ampere
4	NC	No electrical connection
5	GND	Ground

### OUTLINE DRAWING (All dimensions in mm)






**2500-6000MHz/30Watt/Module**

*Model Number: OC-PA2.5-6K30W*

**TYPICAL PERFORMANCE PLOTS (For Reference Only)**



**Note:**

- 1. Adequate heatsink required.