

18000-26500MHz

Model Number: OC-LNA18-26.5K22DB

The model OC-LNA18-26.5K22DB is a broadband, low noise, high P_{-1dB} low noise amplifier operating between 18000 MHz and 26500 MHz and providing an ultra low noise figure with 2.5 dB. The employment of Hetero-Junction FET devices with good noise figure in manufacturing ensures this module exceptional noise figure performance. It is the key component of the electronic system.

FEATURES:

- Broadband;
- Low Noise Figure;
- High Output P_{-1dB};
- Small Size & Light Weight;
- Good Consistency;

ELECTRICAL SPECIFICATIONS @ +12.0VDC, 25°C, 50Ω

Parameter	Symbol	Min	Typ	Max	Units
Operating Frequency	BW	18000		26500	MHz
Small Signal Gain	Gain		22		dB
Small Signal Gain Flatness	Δ G _{ss}			±1.5	dB
Output P _{-1dB}	OP _{-1dB}		10		dBm
Noise Figure	NF		2.5		dB
VSWR @ Input Port	IN VSWR			2.3:1	
VSWR @ Output Port	OUT VSWR			2.3:1	
In/Output Impedance	Impedance		50		Ω
Operating Voltage	VDC		+12		Volt
DC Current	IDD@+12V			100	mA

MECHANICAL SPECIFICATIONS

Parameter	Value	Units	Notes
Dimensions	20x15x10 [0.79x0.59x0.39]	mm [inch]	Maximum
Weight	20 [0.04]	g [lbs]	Maximum
RF Connectors Input	2.92, Female		
RF Connectors Output	2.92, Female		
DC Interface Connector	INSULATOR		

ENVIRONMENTAL CHARACTERISTICS (Design to Meet)

Parameter	Minimum	Typical	Maximum	Units	Notes
Operating Temperature	-20		60	°C	
Non-operating Temperature	-40		65	°C	Storage
Relative Humidity (non-condensing)			95	%	

Absolute Maximum Rating

Input RF drive level without damage	+12 dBm
DC Voltage	+12 V

18000-26500MHz

Model Number: OC-LNA18-26.5K22DB

OUTLINE DRAWING (All dimensions in mm [inch])

