

## 2000-4000MHz

Model Number: OC-LNA1.5-3.5K15DB

The model OC-LNA1.5-3.5K15DB is a broadband, low noise, high P<sub>-1dB</sub> low noise amplifier operating between 2000 MHz and 4000 MHz and providing an ultra low noise figure with 1.7 dB. The employment of Hetero-Junction FET devices with good noise figure in manufacturing ensures this module exceptional noise figure performance. It is the key component of the electronic system.

### FEATURES:

- Broadband;
- Low Noise Figure;
- High Output P<sub>-1dB</sub>;
- Small Size & Light Weight;
- Good Consistency;

### ELECTRICAL SPECIFICATIONS @ +12.0VDC, 25°C, 50Ω

Parameter	Symbol	Min	Typ	Max	Units
Operating Frequency	BW	2000		4000	MHz
Small Signal Gain	Gain	14	15	16	dB
Small Signal Gain Flatness	Δ Gss		±0.5	±0.8	dB
Output P <sub>-1dB</sub>	OP <sub>-1dB</sub>	14	15		dBm
Noise Figure	NF		1.7	2.2	dB
VSWR @ Input Port	IN VSWR			2.0:1	
VSWR @ Output Port	OUT VSWR			2.0:1	
In/Output Impedance	Impedance		50		Ω
Operating Voltage	VDC		+12		Volt
DC Current	IDD@+12V		70	100	mA

### MECHANICAL SPECIFICATIONS

Parameter	Value	Units	Notes
Dimensions	20x15x10 [0.79x0.59x0.39]	mm [inch]	Maximum
Weight	25 [0.06]	g [lbs]	Maximum
RF Connectors Input	SMA, Female		
RF Connectors Output	SMA, Female		
DC Interface Connector	INSULATOR		

### ENVIRONMENTAL CHARACTERISTICS (Design to Meet)

Parameter	Minimum	Typical	Maximum	Units	Notes
Operating Temperature	-20		60	°C	
Non-operating Temperature	-40		70	°C	Storage
Relative Humidity (non-condensing)			95	%	

### Absolute Maximum Rating

Input RF drive level without damage	+15 dBm
DC Voltage	+15 V

2000-4000MHz

Model Number: OC-LNA2-4K15DB

OUTLINE DRAWING (All dimensions in mm [inch])

