

2200-2700MHz/50Watt/Module

Model Number: OC-NPA2.2-2.7K50W

The model OC-NPA2.2-2.7K50W is a high power amplifier operating between 2.2GHz and 2.7GHz and offering a wide dynamic Range with 50Watts typical saturated power. The employment of advanced high power devices in manufacturing ensures this module exceptional power performance, long term reliability and high efficiency.

FEATURES:

- Narrowband & High power;
- High Efficiency;
- Small Size & Light Weight;
- Low Distortion

ELECTRICAL SPECIFICATIONS @ +28.0VDC, 25°C, 50Ω

Parameter	Symbol	Min	Typ	Max	Units
Operating Frequency	BW	2.2		2.7	GHz
RF Output Power	PsAT	45	50		Watt
Power Gain	Gp		47		dB
Power Gain Flatness	Δ Gp		±1.5		dB
Input Return Loss	S ₁₁			-10	dB
Harmonics @30W	H		-20		dBc
Spurious Signals	Spur		-55		dBc
Switch On/Off@10-90% Time	TON/OFF		2		μS
In/Output Impedance	Impedance		50		Ω
Operating Voltage	VDC	24	28	32	Volt
DC Current @50W	IDD		6		Amp

MECHANICAL SPECIFICATIONS

Parameter	Value	Units	Notes
Dimensions	150x90x25 [5.9x3.55x0.98]	mm [inch]	Maximum
Weight	1.5 [3.3]	kg [lbs]	Maximum
RF Connectors Input	SMA, Female		
RF Connectors Output	SMA, Female		
DC Interface Connector	D-Sub 9-Pin, Male		
Cooling	External Heatsink Required (Not Supplied)		

ENVIRONMENTAL CHARACTERISTICS (Design to Meet)

Parameter	Minimum	Typical	Maximum	Units	Notes
Operating Temperature	-20		60	°C	
Non-operating Temperature	-40		65	°C	Storage
Relative Humidity (non-condensing)			95	%	

ABSOLUTE MAXIMUM RATING


Input RF drive level without damage	+5 dBm (Max)
Load VSWR @ POUT =20W	5:1 @ all load phase & amplitude for duration of 1 minutes; 3:1 @ all load phase & amplitude continuous
Over Temperature	85°C @ heatsink [restored @ 60°C]

2200-2700MHz/50Watt/Module

Model Number: OC-NPA2.2-2.7K50W

DC INTERFACE CONNECTOR


Pin #	Description	Specifications
1,2	VDD	28V _{DC}
3,4	GND	Ground
5	SHUTDOWN	Amplifier Disable: TTL Logic High (3.3V) (Internally Pulled-Low)
6	CURRENT MONITOR	Analog voltage relative to I _{DD} @ 100mV per Ampere
7	TEMP MONITOR	Analog voltage relative to Module's Temperature @ 10 mV/°C
8	NC	
9	NC	

OUTLINE DRAWING (All dimensions in mm [inch])

2200-2700MHz/50Watt/Module

Model Number: OC-NPA2.2-2.7K50W

TYPICAL PERFORMANCE PLOTS



Note: Adequate heatsink required.